

1-5 Fletchers Square, Temple Farm Ind Estate,
Sutton Road, Southend-on-Sea,
Essex SS2 5RN
Tel: (01702) 899440 Fax: (01702) 307180

Invoice Name & Address:

Telephone:

Customer Ref:

Date Required:

Previous Quote No:

Works Order No:

Date Received:

Secured By Design ☐ Doc Q compliant ☐

Part L Compliant Products: ☐

BFRC Energy Rated Products: B ☐

Authorised Retailer - Energy Rated Product

AR No:

AR

 B ☐

FRAME CONSTRUCTION: Internally (dummy sashes will be required) or Externally Glazed System

Outer: AW605 53x58mm ☐ AW601 53x70mm ☒ Discontinued Check for stock

Sash: AW614 45mm Int glazed ☐ AW611 56mm Ext glazed ☐

Trans/Mull: AW632 57mm

FRAME FINISH: White (RAL9910 gloss)* ☐

RAL: on White (RAL9910 gloss) ☐

RAL: on RAL: ☐ *RAL9910 Gloss is our standard White

GLAZING BEAD: *Bead type determined if int/ext glazed Square ☐ Bevel ☐

GASKET TYPE: Black ☐ Anthracite Grey ☐

HANDLE TYPE & COLOUR:

STANDARD: ☐ Colour:

CONTEMPORARY: ☐ Handle Type: Colour:

Please see spec sheets on our website for handles styles & colours

Item	O/All Size		Qty	Design No.	Mullion Break	Transom Drop	Glazing		Glass Description (see note re lam glass)	Spacer Bar Colour*	Add on/ Coupler	Cill Type	Cill Length**	Hinge Type		Hinge Guard	Part F Slot Vent in 73mm Head
	Width	Height					U/G	D/G						Egr	Rest		
1																	
2																	
3																	
4																	
5																	

View all Windows from OUTSIDE – including Tilt & Turn Windows

**Std cill length = frame width +100mm

1

2

3

4

5

Floating Mullion Req ☐

Part F ☐ Compliant Slot Vents

Floating Mullion Req ☐

Part F ☐ Compliant Slot Vents

Floating Mullion Req ☐

Part F ☐ Compliant Slot Vents

Floating Mullion Req ☐

Part F ☐ Compliant Slot Vents

Floating Mullion Req ☐

Part F ☐ Compliant Slot Vents

Special Requirements:

Ordering Notes:

Glazing: 28mm glazing as standard. 26.8mm glazed units to be used if laminated glass reqd

*Spacer Bar: Black warm edge spacer bar as standard.

Min/Max Heights: For size limitations see data sheets in the Technical section of our website

Transom/Mullion: AW632 will be used on these windows

Cill Height: 25mm **Cill sizes available: 95 / 150 / 190mm

Locks: Shootbolt locking as standard

Frame Add On: 20mm. 40mm available for 70mm system only. Coupler: 15mm & 26mm available

Important:

Before ordering please ensure that you are familiar with our products and specifications as we will not accept responsibility for want of knowledge in the event that items manufactured do not meet with your requirements. This order cannot be accepted unless signed below.

Signed :