

ENERGY RATINGS - REHAU RIO FLUSH FIT



System	Input Options						Output Data						
	Option 1	Option 2	Option 3	Option 4	Fixed Field (Dependant On Glass Type)	Option 5	Thermal Transmittance	Solar Factor	Window Air Leakage Heat Loss	Label Index	Energy Rating	Report No.	BFRC SEL No.
Profile Type	Frame	Sash		Glass Type									
All Fully Reinforced	Ch = Chambers	Bev = Bevelled TT = Tilt & Turn FS = Fully Sculptured OG = Part Sculptured FR = Fully Reverse	Mullion / Transom	Based on Saint Gobain Products	Unit Centre Pane Value	Spacer Bar Type & Butyl Sealant	U window	G window	L Factor				
Reh Rio/Total70c	52mm 5ch	63mm Flush	69mm	4mm Planilux / 90% Argon / 4mm Total +	1.2 W/m ² .K	Thermobar	1.4 W/m ² .K	0.46	0.21 W/m ² .K	4	A	N/A	SEL A Rated 5911
Reh Rio/Total70c	62mm 5ch	63mm Flush	69mm	4mm Planilux / 90% Argon / 4mm Total +	1.2 W/m ² .K	Thermobar	1.4 W/m ² .K	0.44	0.21 W/m ² .K	1	A	N/A	SEL A Rated 5911
Reh Rio/Total70s	52mm 5ch	63mm Flush	69mm	4mm Planilux / 90% Argon / 4mm Total +	1.2 W/m ² .K	Thermobar	1.4 W/m ² .K	0.46	0.21 W/m ² .K	5	A	N/A	SEL A Rated 5911
Reh Rio/Total70s	62mm 5ch	63mm Flush	69mm	4mm Planilux / 90% Argon / 4mm Total +	1.2 W/m ² .K	Thermobar	1.4 W/m ² .K	0.44	0.21 W/m ² .K	2	A	N/A	SEL A Rated 5911
Reh Rio/Total70c	52mm 5ch	63mm Flush	69mm	4mm Planilux / 90% Argon / 2 x 4mm Total +	0.8 W/m ² .K	Thermobar	1.1 W/m ² .K	0.39	0.21 W/m ² .K	12	A+	N/A	SEL A Rated 5910
Reh Rio/Total70c	62mm 5ch	63mm Flush	69mm	4mm Planilux / 90% Argon / 2 x 4mm Total +	0.8 W/m ² .K	Thermobar	1.1 W/m ² .K	0.38	0.21 W/m ² .K	10	A+	N/A	SEL A Rated 5910
Reh Rio/Total70s	52mm 5ch	63mm Flush	69mm	4mm Planilux / 90% Argon / 2 x 4mm Total +	0.8 W/m ² .K	Thermobar	1.1 W/m ² .K	0.39	0.21 W/m ² .K	13	A+	N/A	SEL A Rated 5910
Reh Rio/Total70s	62mm 5ch	63mm Flush	69mm	4mm Planilux / 90% Argon / 2 x 4mm Total +	0.8 W/m ² .K	Thermobar	1.1 W/m ² .K	0.38	0.21 W/m ² .K	10	A+	N/A	SEL A Rated 5910

